



NCS6742 N4

**NETAŞ CLOUD
SERVER**

DATASHEET

NCS6742 N4, is a new-generation 4U2 socket general rack server, which supports 2 Intel® Xeon® 4/5 generation scalable processor (Eagle Stream).

NCS6742 N4 uses a high-density, modular, and streamline design.

Enterprise level 4U large-storage server, it features high capability, large capacity, high reliability, easy expansion, and easy management, which is widely applicable to interconnection, network, cloud computing, big data, and virtualization.

1. High Density, High Performance

- Supports two Intel 4th/5th Generation of Intel® Xeon® Scalable Processors (Eagle Stream)
- Supports a maximum of 120 physical cores and hyper-threading in dual-way mode to meet the cloud computing deployment requirements.
- Provides 32 DDR5 memory slots, with a maximum rate of 4,800MT/s
- Supports a maximum of 24 NVMe U.2 hard disks, provides high-speed I/O interfaces and solves the bottleneck of slow access to traditional hard disks.

2. High Availability, High Reliability

- Supports diversified storage topologies and storage types, and supports a maximum of 44 2.5/3.5-inch hot-swappable hard disks.
- Supports the expansion of thirteen PCIe slots and the PCIe Gen5 protocol to meet the flexible expansion requirements such as network and storage control.
- Supports a maximum of two double-width or four single-width GPU cards to provide powerful heterogeneous computing capabilities.

3. Convenient Management, Easy Maintenance

- Comprehensively monitors system health so that core components can be monitored and diagnosed.
- Supports automatic deployment, firmware upgrade, and remote operations to improve deployment and O&M efficiency.
- Provides enterprise-level management functions and reliability, automatic equipment on-duty observation, real-time monitoring of core components, and makes streamline classification and reporting of faults, providing comprehensive guarantee for data center O&M.

4. Green, Energy Saving, Environment Protection

- Adopts 80PLUS high-efficiency power modules to support high-voltage DC and low-voltage DC technologies to improve energy utilization.
- Selects high-efficiency fans so that under the same heat dissipation capability, the power consumption is lower.
- Intelligent rotation speed adjustment and silence design
- Lead-free design and environmental protection



5. Technical Specifications

Technical Specification	NCS6742 N4 4U Rack Server
Feature	
From	4U Rack Server
Applicable Cabinet	19 inches >=1.000m - deep cabinet
Processor	Supports ½ Intel® Xeon® 4th/5th generation scalable processor (Eagle Stream)
Interconnection bus	Supports 3 channel UPI 2.0 interconnection links at maximum rate of 16GT/s
Memory	Support up to 32 DDR5 memory slots with maximum rate of 4,800 MT/s
Raid controller	Supports RAID 0/1/5/6/10/50/60 and power-off protection
Local Storage	Provides a maximum of 24x 2.5"/3.5" slots (front), or maximum of 12x 2.5"/3.5" slots (rear), + 4x 2.5" slots,
I/O Module	
Network Resources	Supports 2x OCP3.0 interfaces, Supports PCIE5.0
PCIe slots	Supports up to 13 PCIe slots: 2x OCP dedicated slots, 1x dedicated Raid card slot
External Equipment interface	4x USB interface 2x rear USB3.0 1x front USB3.1 1x front USB2.0 2x VGA interface (1x front, 1x rear) 1x RS232 - Serial port
Hardware Management Interface	Support 1 independent GE management network interface
Display	Integrated display controller (1,920x1,080),

OS	
Compatible OS	Compatible with mainstream server operating systems: Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Enterprise Linux, Vmware ESXI, CGSL, Centos, Kylin
Physical Features	
Power	Supports 1+1 hot/swappable redundant power supplies. (Optional) 800 W/1200 W/1600 W/2000 W/2700 W, high-efficiency platinum/titanium power supply Supports 110V/220V AC, 240V/336V high-voltage DC and -48V DC
Fan	4 or 8 of high-efficiency fans, N+1 redundancy and intelligent heat dissipation system
Environmental conditions	Operating temperature: +5 °C to +45 °C (depending on the configuration, refer to the technical documentation for details) Storage temperature: -40 °C to +65 °C Operating humidity: %8 – %90 RH, no condensation Transportation and storage humidity: %5 – %95 RH, no condensation Altitude: ≤ 3.000m. When the altitude is 900m. higher, the operating temperature is reduced by 1°C for every 300m. higher. If the altitude is more than 3.000m., you cannot configure mechanical hard disks.
Size	447.6 mm x 175 mm x 780 mm (W x H x D), excluding flanges and guide rails, 482.6 mm x 175 mm x 791.6 mm (W x H x D) including flanges Standard 19-inch rack (>=1m deep)
Weight with full configuration	The equipment with the maximum configuration is about 60Kg. (Excluding guide rails)
Certificate	CE, CCC, CQC, RosH